

HOLD

One-hand temperature measuring instrument

testo 105

Ideally suited to applications in the food sector

Exchangeable measurement tips

2 freely adjustable limit values

Audible and optical alarm

One-line display, illuminated

Especially robust, can be cleaned under running water (according to protection class IP65)

Certified according to EN 13485




The testo 105 is a robust food thermometer with exchangeable measurement tips for temperature measurement on semi-solid media. It has an additional measurement tip for frozen goods. Depending on the probe used, it is particularly suited to applications in the areas of gastronomy, refrigerated rooms, large kitchens, supermarkets and the checking of Incoming Goods.

Since it can be cleaned under running water according to IP65, it is especially hygienic, and applicable everywhere, thanks to its robustness. An audible and an optical alarm reliably warn when individually adjustable upper and lower limit values are violated.

Set

Technical data / Accessories



Sensor type	NTC
Measuring range	-50 to +275 °C
Accuracy ±1 digit	±0.5 °C (-20 to +100 °C) ±1 °C (-50 to -20.1 °C) ±1 % of mv (+100.1 to +275 °C)
Resolution	0.1 °C

General technical data		
Operating temperature	-20 to +50 °C	
Storage temperature	-40 to +70 °C	
Battery type	Button cell LR44	
Battery life	80 h	
Auto Off	10 min	
Dimensions	145 x 38 x 195 mm	
Display	LCD, 1 line	
Weight	139 g	
Protection class	IP65	
Warranty	2 years	
Standard	EN 13485	

Part no.

Set testo 105, one-hand thermometer with standard measurement tip, frozen food tip, long measurement tip and belt/wall holder and aluminium case	0563 1052	
testo 105, one-hand thermometer with frozen food measurement tip, belt/wall holder and batteries	0563 1054	

Accessories	Part no.		
Accessories for measuring instrument			
Standard measurement tip, 100 mm long	0613 1051		
Frozen food tip, 90 mm long	0613 1052		
Long measurement tip, 200 mm long	0613 1053		
ISO calibration certificate/temperature; for air/immersion probes, calibration points -18°C; 0°C	0520 0041		
Button cell batteries, Type LR 44, 1.5 Volt (4 off)	0515 0032		